

External Transparent Straight Connector

Direct Buried / Push Fit

General Data

Item	Straight Connector
Description	A straight connector which is suitable for connecting a wide range of external duct, providing protection against gas and water up to 15 bar. The HellermannTyton range of straight connectors are fitted with a locking ring which is quick and simple to fit.

Product Specification

Material	Polycarbonate PC				
Part Code		Diameter	Length	Unit	Pack Size
Dimensions	MDC-5MM-EXT	16.8	35.2	mm	100
	MDC-7MM-EXT	18.8	39.1		
	MDC-8MM-EXT	18.8	39.1		
	MDC-10MM-EXT	22.2	46.4		
	MDC-12MM-EXT	25.0	49.2		
	MDC-14MM-EXT	26.7	50.2		
	MDC-16MM-EXT	29.2	55.6		
	MDC-18MM-EXT	32.0	59.1		50
	MDC-20MM-EXT	34.0	62.0		
MDC-25MM-EXT	41.2	71.0			
Pressure	0.5 (permanent gas and watertight)			Bar	
	15 / 30			Bar / Min	
Burst Pressure	Min. 30			Bar	
Tensile Strength	MDC-5MM-EXT	Min. 120		N	
	MDC-7MM-EXT	Min. 300			
	MDC-8MM-EXT	Min. 300			
	MDC-10MM-EXT	Min. 400			
	MDC-12MM-EXT	Min. 450			
	MDC-14MM-EXT	Min. 500			
	MDC-16MM-EXT	Min. 600			
	MDC-18MM-EXT	Min. 600			
	MDC-20MM-EXT	Min. 600			
MDC-25MM-EXT	Min. 800				